



# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 07/10/2018

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** STONETECH® Epoxy Grout Haze & Coating Stripper

#### 1.2. Intended Use of the Product

Cleaner, for professional use only.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

##### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

#### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency Call CHEMTREC day or night

Within USA and Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1A H317

Repr. 1 H360

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H360 - May damage fertility or the unborn child.

H412 - Harmful to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a POISON CENTER or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
2-Butoxyethanol	(CAS-No.) 111-76-2	5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Lactic acid	(CAS-No.) 50-21-5	3 - 7	Skin Irrit. 2, H315 Eye Dam. 1, H318
Diethylene glycol monobutyl ether	(CAS-No.) 112-34-5	2.8 – 2.9	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Alcohols, C9-11, ethoxylated	(CAS-No.) 68439-46-3	0.5 – 1.5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Aquatic Acute 2, H401
1-Methyl-2-pyrrolidone	(CAS-No.) 872-50-4	0.96 - 0.98	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H335
D-Limonene	(CAS-No.) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Quartz	(CAS-No.) 14808-60-7	< 0.025	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	(CAS-No.) 55965-84-9	0.0027 - 0.003	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Skin sensitization. Causes skin irritation. Causes serious eye damage. May damage fertility. May damage the unborn child.

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** May damage fertility or the unborn child.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. chlorinated compounds. Acrid smoke and irritating fumes.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

#### Reference to Other Sections

Refer to Section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

##### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

##### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area.

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Do not breathe vapors, mist, or spray. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Keep container closed when not in use.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Cleaner, for professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	120 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	121 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (ppm)	30 ppm

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Nunavut</b>	OEL TWA (ppm)	20 ppm
<b>Northwest Territories</b>	OEL STEL (ppm)	30 ppm
<b>Northwest Territories</b>	OEL TWA (ppm)	20 ppm
<b>Ontario</b>	OEL TWA (ppm)	20 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	20 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	20 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	30 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	20 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	150 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	50 ppm
<b>D-Limonene (5989-27-5)</b>		
<b>USA AIHA</b>	WEEL TWA (ppm)	30 ppm
<b>Diethylene glycol monobutyl ether (112-34-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Manitoba</b>	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Nova Scotia</b>	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Ontario</b>	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Prince Edward Island</b>	OEL TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>		
<b>USA ACGIH</b>	Biological Exposure Indices (BEI)	100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: end of shift
<b>USA AIHA</b>	WEEL TWA (ppm)	10 ppm
<b>USA AIHA</b>	AIHA chemical category	skin notation
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	125 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	100 ppm
<b>Quartz (14808-60-7)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable fraction)
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
<b>USA ACGIH</b>	ACGIH chemical category	A2 - Suspected Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable fraction)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable dust)
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	300 particle/mL
<b>Silica, crystalline (general form)</b>		
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup> (excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays)

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Off white to light green paste
<b>Odor</b>	: Citric
<b>Odor Threshold</b>	: Not available
<b>pH</b>	: 4
<b>Evaporation Rate</b>	: Not available
<b>Melting Point</b>	: Not applicable
<b>Freezing Point</b>	: Not available
<b>Boiling Point</b>	: Not applicable
<b>Flash Point</b>	: Not applicable
<b>Auto-ignition Temperature</b>	: Not available
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not applicable
<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20°C</b>	: Not available
<b>Relative Density</b>	: Not available
<b>Specific Gravity</b>	: 1.01
<b>Solubility</b>	: Water: Complete
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: 18240 cP

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.

**10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Acrid smoke and irritating fumes. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Hydrogen chloride. Oxides of aluminum. Silicon oxides. Hydrocarbons. Aldehydes, ketones. Organic acids.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**pH:** 4

**Eye Damage/Irritation:** Causes serious eye damage.

**pH:** 4

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** May damage fertility or the unborn child.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Lactic acid (50-21-5)</b>	
LD50 Oral Rat	3543 mg/kg
LC50 Inhalation Rat	> 7.94 mg/l/4h
<b>Alcohols, C9-11, ethoxylated (68439-46-3)</b>	
LD50 Oral Rat	1400 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
<b>2-Butoxyethanol (111-76-2)</b>	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rabbit	435 mg/kg
LC50 Inhalation Rat	2.2 mg/l/4h
LC50 Inhalation Rat	486 ppm/4h
<b>D-Limonene (5989-27-5)</b>	
LD50 Oral Rat	4400 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
LD50 Oral Rat	5660 mg/kg
LD50 Dermal Rabbit	2700 mg/kg
ATE US/CA (dermal)	2,700.00 mg/kg body weight
<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
LD50 Oral Rat	53 mg/kg
ATE US/CA (dermal)	300.00 mg/kg body weight

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

ATE US/CA (dust, mist)	0.50 mg/l/4h
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LD50 Oral Rat	4150 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg
LC50 Inhalation Rat	5.1 mg/l/4h
LC50 Inhalation Rat	5.1 mg/l/4h
<b>Quartz (14808-60-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
<b>2-Butoxyethanol (111-76-2)</b>	
IARC Group	3
<b>D-Limonene (5989-27-5)</b>	
IARC Group	3
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.
<b>Quartz (14808-60-7)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
<b>Silica, crystalline (general form)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

<b>Lactic acid (50-21-5)</b>	
LC50 Fish 1	130 mg/l
<b>Alcohols, C9-11, ethoxylated (68439-46-3)</b>	
LC50 Fish 1	6 - 12 mg/l (Exposure time : 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	2.217 - 3.523 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>2-Butoxyethanol (111-76-2)</b>	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
<b>D-Limonene (5989-27-5)</b>	
LC50 Fish 1	0.619 (0.619 - 0.796) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.421 mg/l
LC50 Fish 2	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
LC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LC50 Fish 1	832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC Chronic Crustacea	12.5 mg/l



# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 12.2. Persistence and Degradability

STONETECH® Epoxy Grout Haze & Coating Stripper	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

STONETECH® Epoxy Grout Haze & Coating Stripper	
Bioaccumulative Potential	Not established.
<b>2-Butoxyethanol (111-76-2)</b>	
Log Pow	0.81 (at 25 °C)
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
BCF Fish 1	(no bioconcentration expected)
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Log Pow	-0.46 (at 25 °C)

12.4. Mobility in Soil Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

STONETECH® Epoxy Grout Haze & Coating Stripper	
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization Health hazard - Skin corrosion or Irritation Health hazard - Reproductive toxicity Health hazard - Serious eye damage or eye irritation
<b>Lactic acid (50-21-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Alcohols, C9-11, ethoxylated (68439-46-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under Chemical Data Reporting Rule (formerly the Inventory Update Reporting Rule), i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 711).
<b>2-Butoxyethanol (111-76-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>D-Limonene (5989-27-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1 %
<b>Quartz (14808-60-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Quartz (14808-60-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Silica, crystalline (general form)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>2-Butoxyethanol (111-76-2)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Quartz (14808-60-7)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

### 15.3. Canadian Regulations

<b>Lactic acid (50-21-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Alcohols, C9-11, ethoxylated (68439-46-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>2-Butoxyethanol (111-76-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>D-Limonene (5989-27-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Quartz (14808-60-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest** : 07/10/2018

**Revision**

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1	Reproductive toxicity, Category 1
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation

# STONETECH® Epoxy Grout Haze & Coating Stripper

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H350	May cause cancer
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US, Mex)