

**Trade name :** Lithofin MN Stain-Stop

Revision date : 12.08.2022

Version (Revision) : 4.2.6 (4.2.5)

Print date : 08.12.2023

**SECTION 1: Identification of the substance/mixture and of the company/ undertaking****1.1 Product identifier**

Lithofin MN Stain-Stop

**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses**

Mixture Impregnation, Contains: organic solvents

**1.3 Details of the supplier of the safety data sheet**

**Distributor :** CDK Stone Pty Ltd  
**Street :** 4-6 Freighter Rd  
**Postal code/City :** Moorabbin, Victoria 3189  
**Country :** AUSTRALIA  
**Telephone :** +61 3 8552 6000  
**Telefax :** +61 3 8552 6001  
**Contact :** Technical Department  
**E-mail :** enquiries@cdkstone.com.au

**Emergency telephone number :** **+61 3 8552 6000**  
(Only available during office hours)

**Supplier :** Lithofin AG  
**Street :** Heinrich-Otto-Str. 36  
**Postal code/City :** 73240 Wendlingen  
**Country :** GERMANY  
**Telephone :** +49 7024 9403 0  
**Telefax :** +49 7024 9403 40  
**Contact :** Technical Department  
**E-mail :** info@lithofin.de

**Emergency telephone number :** **+49 7024 9403 0**  
(Only available during office hours)

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

**Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**Remark**

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

**2.2 Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

## Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

## Signal word

Danger

## Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

## Hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.

## Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....  
P331 Do NOT induce vomiting.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local and national regulations.

## Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

## Other labelling

### 2.3 Other hazards

#### Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

#### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 2.4 Additional information

see section 12.5

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; REACH No. : 01-2119463258-33-xxxx ; EC No. : 919-857-5; CAS No. : (64742-48-9)

Weight fraction :  $\geq 75 - < 80 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 EUH066

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29-xxxx ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction :  $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; REACH No. : 01-2119472146-39-xxxx ; EC No. : 918-167-1; CAS No. : (64742-48-9)

Weight fraction :  $\geq 1 - < 5 \%$

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Aquatic Chronic 4 ; H413 EUH066  
Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; REACH No. : 01-2119456810-40-xxxx ; EC No. : 920-901-0; CAS No. : (64742-48-9)  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 EUH066  
ETHYL ACETATE ; REACH No. : 01-2119475103-46-xxxx ; EC No. : 205-500-4; CAS No. : 141-78-6  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066  
(2-METHOXYMETHYLETHOXY)PROPANOL ; REACH No. : 01-2119450011-60-xxxx ; EC No. : 252-104-2; CAS No. : 34590-94-8  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Substance with a community workplace exposure limit

### Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

None (below the concentration limit)

### Contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH

None (below the concentration limit)

### Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.  
< 0,1% Benzene, Regulation (EC) No. 1272/2008, Annex VI; J, P  
For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice. Observe risk of aspiration if vomiting occurs.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

#### Following ingestion

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes for the doctor

Treat symptomatically.

#### Special treatment

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

**5.1 Extinguishing media**

**Suitable extinguishing media**

Foam Carbon dioxide (CO<sub>2</sub>) BC-powder ABC-powder Water spray jet

**Unsuitable extinguishing media**

Full water jet Strong water jet

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

Carbon monoxide Carbon dioxide (CO<sub>2</sub>) Hydrogen fluoride Fluoropolymers

**5.3 Advice for firefighters**

Use suitable breathing apparatus.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

**6.2 Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up**

**For cleaning up**

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Measures to prevent fire**

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition - No smoking. The product is: Combustible

**Fire class :** B

**Shake well before use** nein

**Advices on general occupational hygiene**

P362+P364 - Take off contaminated clothing and wash it before reuse.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

**Trade name : Lithofin MN Stain-Stop**

Revision date : 12.08.2022  
Print date : 08.12.2023

Version (Revision) : 4.2.6 (4.2.5)

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

**Hints on joint storage**

**Storage class (TRGS 510) :** 3

**Protect from frost** nein

**Recommended storage temperature** 5 - 25 °C

**Further information on storage conditions**

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

**7.3 Specific end use(s)**

**Recommendation**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type (country of origin) : KZG ( D )

Limit value : 100 ppm / 600 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : MAK ( D )

Limit value : 50 ppm / 300 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 300 mg/m<sup>3</sup>

Peak limitation : 2(II)

Version :

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : KZG ( D )

Limit value : 150 ppm / 720 mg/m<sup>3</sup>

Remark : SSc

Version :

Limit value type (country of origin) : MAK ( D )

Limit value : 50 ppm / 240 mg/m<sup>3</sup>

Remark : SSc

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 62 ppm / 300 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

Version : 23.06.2022

Limit value type (country of origin) : STEL ( EC )

Limit value : 150 ppm / 723 mg/m<sup>3</sup>

Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )

Limit value : 50 ppm / 241 mg/m<sup>3</sup>

Version : 20.06.2019

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 600 mg/m<sup>3</sup>

Version :

Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 600 mg/m<sup>3</sup>

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Version :  
ETHYL ACETATE ; CAS No. : 141-78-6  
Limit value type (country of origin) : KZG ( D )  
Limit value : 400 ppm / 1460 mg/m<sup>3</sup>  
Remark : SSc  
Version :  
Limit value type (country of origin) : MAK ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Remark : SSc  
Version :  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 23.06.2022  
(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8  
Limit value type (country of origin) : KZG ( D )  
Limit value : 50 ppm / 300 mg/m<sup>3</sup>  
Version :  
Limit value type (country of origin) : MAK ( D )  
Limit value : 50 ppm / 300 mg/m<sup>3</sup>  
Version :  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 50 ppm / 310 mg/m<sup>3</sup>  
Peak limitation : 1(I)  
Version : 23.06.2022  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 308 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

## DNEL-/PNEC-values

### DNEL/DMEL

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 125 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 125 mg/kg bw/day  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 185 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 208 mg/kg bw/day  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 871 mg/m<sup>3</sup>

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Exposure frequency : Long-term  
Limit value : 102,3 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 859,7 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 480 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 960 mg/m<sup>3</sup>

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 4,5 mg/kg/d  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 734 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 37 mg/kg/d  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 367 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 734 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 1468 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 1468 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 63 mg/kg/d  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 734 mg/m<sup>3</sup>

**PNEC**

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,18 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 0,36 mg/l  
Limit value type : PNEC (Aquatic, marine water)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Limit value :	0,018 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	0,981 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,0981 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	35,6 mg/l
ETHYL ACETATE ; CAS No. : 141-78-6	
Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	0,24 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	1,65 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	0,024 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	1,15 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,115 mg/kg
Limit value type :	PNEC (Soil)
Limit value :	0,148 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	650 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

Eye glasses with side protection goggles

##### Required properties

EN 166

#### Skin protection

##### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** NBR (Nitrile rubber), 0,4mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

**Required properties :** EN ISO 374

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

##### Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** antistatic.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

**Remark :** Barrier creams are not substitutes for body protection.

#### Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

**Suitable respiratory protection apparatus**



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Full-/half-/quarter-face masks (EN 136/140) Combination filtering device (EN 14387) ABEK-P1 (EN14387)

## Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** Liquid

**Colour :** light yellow

**Odour :** solvent

#### Safety characteristics

<b>Melting point/freezing point :</b>	( 1013 hPa )	<	-18	°C	
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	approx.	160	°C	
<b>Decomposition temperature :</b>	( 1013 hPa )		not determined		
<b>Flash point :</b>		approx.	24	°C	closed cup (EN ISO 3679)
<b>Auto-ignition temperature :</b>			not determined		
<b>Sustaining combustion</b>			Yes		UN Test L2:Sustained combustibility test
<b>Lower explosion limit :</b>			not determined		
<b>Upper explosion limit :</b>			not determined		
<b>Vapour pressure :</b>	( 50 °C )	<	3000	hPa	
<b>Density :</b>	( 20 °C )		0,8	g/cm <sup>3</sup>	Pyknometer (DIN EN ISO 2811-1)
<b>Solvent separation test :</b>	( 20 °C )	<	3	%	Test L1: Solvent separation test (UN)
<b>Water solubility</b>	( 20 °C )		hydrolysed		
<b>pH :</b>			not applicable		DIN 19268
<b>log P O/W :</b>			not determined		(Mixture)
<b>Flow time :</b>	( 23 °C )	<	15	s	ISO cup 4 mm (DIN EN ISO 2431)
<b>Odour threshold :</b>			not determined		
<b>Vapourisation rate :</b>			not determined		
<b>VOC content-EC</b>			87,1	Weight-%	*
<b>VOC content-EC</b>			694	g/l	*
<b>VOC-France</b>			A+		Décret no 2011-321 du 23 mars 2011

(\* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

### 9.2 Other information

Data apply to the main component:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS: 64742-48-9)

Lower explosion limit (Vol-%): 0,6

Upper explosion limit (Vol-%): 6,0

log P O/W: 5,0 - 6,7

## SECTION 10: Stability and reactivity

**Trade name : Lithofin MN Stain-Stop**

Revision date : 12.08.2022  
Print date : 08.12.2023

Version (Revision) : 4.2.6 (4.2.5)

**10.1 Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3 Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**10.4 Conditions to avoid**

Stable under recommended storage and handling conditions.

**10.5 Incompatible materials**

No data available

**10.6 Hazardous decomposition products**

Does not decompose when used for intended uses.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Acute oral toxicity**

Parameter :	LD50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	10760 mg/kg
Method :	OECD 423
Parameter :	LD50 ( Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Exposure route :	Oral
Effective dose :	> 5000 mg/kg
Parameter :	LD50 ( Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Exposure route :	Oral
Effective dose :	> 5000 mg/kg
Parameter :	LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	5600 mg/kg

**Acute dermal toxicity**

Parameter :	LD50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 5000 mg/kg
Parameter :	LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 14112 mg/kg
Method :	OECD 402
Parameter :	LD50 ( Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Exposure route :	Dermal

**Trade name : Lithofin MN Stain-Stop**

Revision date : 12.08.2022

Version (Revision) : 4.2.6 (4.2.5)

Print date : 08.12.2023

Effective dose : > 5000 mg/kg  
Parameter : LD50 ( Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )  
Exposure route : Dermal  
Effective dose : > 5000 mg/kg  
Parameter : LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 18000 mg/kg

**Acute inhalation toxicity**

Parameter : LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 23,4 mg/l  
Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 58 mg/l  
Exposure time : 8 h

**Specific effects (Longterm animal experiment)**

There are no data available on the preparation/mixture itself.

**Corrosion**

Based on available data, the classification criteria are not met.

**Assessment/classification**

Repeated exposure may cause skin dryness or cracking.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**Repeated dose toxicity (subacute, subchronic, chronic)**

There are no data available on the preparation/mixture itself.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Carcinogenicity**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

No information available.

**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity**

Based on available data, the classification criteria are not met.

**Chronic (long-term) fish toxicity**

**Trade name :** Lithofin MN Stain-Stop

Revision date : 12.08.2022

Version (Revision) : 4.2.6 (4.2.5)

Print date : 08.12.2023

Parameter :	NOEC ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Fish
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Fish
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Fish
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Fish
Effective dose :	> 9,65 mg/l
Exposure time :	32 D

**Chronic (long-term) toxicity to aquatic invertebrate**

Parameter :	NOEC ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 0,1 - 1 mg/l
Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Daphnia
Effective dose :	2,4 mg/l
Exposure time :	21 D

**Acute (short-term) toxicity to algae and cyanobacteria**

Parameter :	EC50 ( Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 1000 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Species :	Daphnia
Effective dose :	44 mg/l
Exposure time :	48 h
Parameter :	EC50 ( Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 100 mg/l
Parameter :	EC50 ( Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (64742-48-9) )
Species :	Daphnia
Effective dose :	> 100 mg/l
Parameter :	EC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Daphnia
Effective dose :	610 mg/l
Exposure time :	48 h

**Chronic (long-term) toxicity to aquatic algae and cyanobacteria**

Parameter :	NOEC ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Species :	Algae

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

Effective dose : > 100 mg/l  
Exposure time : 72 h  
Method : OECD 201

## Sewage treatment plant

Observe local regulations concerning effluent treatment.

## 12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

### Biodegradation

There are no data available on the preparation/mixture itself.

## 12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

## 12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

No information available.

## 12.7 Other adverse effects

There are no data available on the preparation/mixture itself.

## 12.8 Additional ecotoxicological information

### Additional information

The product has not been tested.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

##### Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 01 04\* (other organic solvents, washing liquids and mother liquors)

##### After intended use

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

##### Disposal operations

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

##### Waste codes/waste designations according to EWC/AVV

Waste code packaging: 15 01 10\*

### 13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

## SECTION 14: Transport information

### 14.1 UN number or ID number

UN 1993

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · N-BUTYL ACETATE)

#### Sea transport (IMDG)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

Revision date : 12.08.2022

Version (Revision) : 4.2.6 (4.2.5)

Print date : 08.12.2023

FLAMMABLE LIQUID, N.O.S. ( TURPENTINE SUBSTITUTE · N-BUTYL ACETATE )

#### Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. ( TURPENTINE SUBSTITUTE · N-BUTYL ACETATE )

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special Provisions : LQ 5 I · E 1  
Hazard label(s) : 3

#### Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / ~~S-E~~  
Special Provisions : LQ 5 I · E 1  
Hazard label(s) : 3

#### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special Provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

None

### 14.7 Maritime transport in bulk according to IMO instruments

Not required.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)  
DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC)  
EN 2:1992 (DIN EN 2:2005-01)

#### Authorisations and/or restrictions on use

##### Restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 75

##### Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### Other regulations (EU)

Regulation (EC) No. 648/2004 [Detergents regulation]  
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

### Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer

Not listed/not relevant.

Contains the following substances that deplete the ozone layer: -

### Regulation (EC) 2019/1021 [POP Regulation]

Not listed/not relevant.

Name of the persistent organic pollutant (POP): -

### Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

Not listed/not relevant.

### Regulation (EU) 649/2012 (PIC)

Not listed/not relevant.

Chemicals qualifying for PIC notification: -

### National regulations

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

### Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

### Other regulations, restrictions and prohibition regulations

#### Switzerland

#### VOCV-Regulation

Maximum VOC content (Switzerland) : 87,1 Weight-% according to VOCV

## 15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

## 15.3 Additional information

## SECTION 16: Other information

### 16.1 Indication of changes

07. Hints on joint storage - Storage class

### 16.2 Abbreviations and acronyms

ABC-Pulver	Extinguishing powder for fire class A, B and C
ABEK-P1	combination filter
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)
AWSV	Ordinance on facilities for the handling of substances hazardous to water
BGR	BG rules and regulations
ca.	circa
CAS	Chemical Abstracts Service
CLP	classification, labelling and packaging
CMR	Carcinogen, mutagen or toxic for reproduction
DIN	German Institute for Standardization
DNEL	Derived No-Effect Level
EAK/EWC/EAC/CWR/CER	European Waste Catalogue
EC50 / CE50	Effective Concentration 50%
EG / EC / CE	European Community
EN	European Standard
EUH	supplemental hazard statement of the european union
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

GHS / SGH	Globally Harmonised System
H-Sätze	hazard statements
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization-Technical Instructions
IMDG-Code	International Maritime Dangerous Goods Code
ISO	International Organization for Standardization
LC50 / CL50	Lethal Concentration 50%
LD50 / DL50	Lethal Dose 50%
log P O/W	Partition coefficient n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (marine pollution)
NOAEL (DSET)	No observed adverse effect level
NOEC (CSEO)	No observed effect concentration
Nr.	Number
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative and toxic
pH	Potentia hydrogenii
PIC	prior informed consent
PNEC	Predicted No-Effect Concentration
POP	Persistent organic pollutants
P-Sätze	precautionary statements
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## 16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL  
ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)  
REACH Article 59: Candidate List of substances of very high concern for Authorisation  
(<https://echa.europa.eu/candidate-list-table>)

## 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data.  
Hazard statements for health hazards : Calculation method.  
Hazard statements for environmental hazards : Calculation method.

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.



# Safety Data Sheet

( EN / D )

according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** Lithofin MN Stain-Stop

**Revision date :** 12.08.2022

**Version (Revision) :** 4.2.6 (4.2.5)

**Print date :** 08.12.2023

---

H336	May cause drowsiness or dizziness.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

## 16.6 Training advice

None

## 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---