

# RLA FILLET & JOINT SEAL

## Fast Curing Low Modulus Sealant



### **DESCRIPTION:**

RLA FILLET AND JOINT SEAL is a grey fast, curing, low modulus sealant that cures from moisture in the air to form a tough, elastic, and water-resistant sealant before the application of RLA polyurethane and waterproofing membranes.

### **FEATURES AND BENEFITS:**

- High durability
- Excellent weather resistance
- Non-staining
- Fast cure

### **RECOMMENDED USES:**

- Fillet joints to Internal wet areas to AS3740
- Fillet Joints to External wet areas to AS4654
- Expansion & control joints to internal wet areas
- Filling of static cracks & sheet joins in internal wet areas.

### **SURFACE PREPARATION:**

Clean all surfaces by removing foreign matter and contaminants such as oil, dust, grease, frost, water, surface dirt, old sealants, and any protective coating. Porous substrates should be cleaned by grinding saw cutting or blast cleaning (sand or water).

Dust, loose particles, etc., should be blown out of joints with oil-free compressed air or vacuum cleaned. Non-porous and plastic surfaces should be cleaned by solvent or mechanical means. Cleaning solvents should not be allowed to air dry or evaporate without being wiped with a clean, dry cloth.

### **PRIMING:**

For maximum performance on porous or non-porous surfaces, [RLA PU PRIMER](#) is recommended, including for non-porous metallic & hard plastic substrates.

### **COVERAGE:**

(Excluding waste or substrate irregularities.)

600ml sausage:

15mm x 15mm Fillet Approx. 5.3 metres 20mm x 20mm

Fillet Approx. 3.0 metres

### **APPLICATION:**

Place RLA FILLET AND JOINT SEAL sausage into an appropriate barrel gun and clip the end of the sausage. Screw the top of the nozzle and housing onto the barrel gun. Cut off the nozzle at the tip at a 45° angle to desired thickness.

Apply RLA FILLET AND JOINT SEAL in a continuous operation using firm pressure on the gun's trigger to appropriately fill the static crack, joint or internal angle of the wet area.

Cracks must be ground out a minimum of 3mm, vacuumed and cleaned to remove all debris, and filled to a minimum of 6mm depth. Joints must be a minimum of 6mm in width and depth. Fillet joints must span any gaps or joints between horizontal & vertical substrates within the wet area and extend a minimum of 6mm on either side of the gap or joint.

### **CLEAN UP:**

Clean tools and equipment with RLA Handy Wipes while the sealant is still wet.

### **SHELF LIFE / STORAGE:**

12 months when stored in original unopened packaging To be stored in a dry area off the ground.

### **PACKAGING:**

600ml sausages-product code:620529

### **SAFETY & HANDLING:**

- Wear suitable respiratory protection.
- Use in well-ventilated areas.
- Avoid breathing vapours
- Avoid contact with skin and eyes.
- Wear eye protection and suitable gloves and clothing.
- Do not eat, drink, or smoke while using this product.
- If on the skin, wash with plenty of soap and water.
- If in the eyes: rinse cautiously with water for several minutes.
- Remove contact lenses; if present, continue rinsing.
- If any skin or eye irritation persists or you feel unwell, get medical attention.

**The Safety Data Sheet is available upon request.**

**FIRST AID:**

If poisoning occurs, contact a doctor or Poisons Information Centre.

Skin: Wash off with warm water and soap.

If swallowed, DO NOT induce vomiting. Give a glass of water.

For advice or if you feel unwell, contact a Poisons Information Centre: Australia ph. 131126,  
New Zealand ph. 0800 764 766 or a doctor at once.

If swallowed, do NOT induce vomiting.

IF SWALLOWED, immediately call the Poisons Information Centre or a doctor.

IF ON SKIN Remove immediately all contaminated clothing and wash skin with soap and water.

If skin irritation occurs, get medical advice/attention.

IF IN EYES Rinse carefully with water for several minutes.

If eye irritation persists, get medical advice/attention.

**WARRANTY STATEMENT:**

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specifications.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out per the relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

**PHONE:** 1800 242 931

**EMAIL:** [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au)

**MAIL:** 215 Colchester Road Kilsyth Victoria 3137 (Attention Customer Service)

**WEBSITE:** [www.rlapolymers.com.au](http://www.rlapolymers.com.au)

**AUSTRALIAN CONSUMER LAW:**

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

**DISCLAIMER:**

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.



Quality  
ISO 9001  
SAI GLOBAL

RLA FILLET & JOINT SEAL

RLA Polymers Pty Ltd ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria, 3137 [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au)

T. 1800 242 931

[rlapolymers.com.au](http://rlapolymers.com.au)

Version:01

Issue Date 08/11/2022



NANPAO

PART OF THE NAN PAO GROUP